

Trulawn Adventure Artificial Grass by Devon Artificial Grass

Product info:

Soft non-abrasive grass which is ideal for play areas with heavy traffic.

- | | | |
|---|-------------|-----------------------------------|
| • | Appearance | For play areas with heavy traffic |
| • | Colour | Olive green with a tan thatch |
| • | Weight | 2.8kg per square metre |
| • | Yarn | Polyethylene and Polypropylene |
| • | Guarantee | 8 years |
| • | Pile Height | 32mm |

PRODUCT INFORMATION FOR REFERENCE ONLY.
ALL INFORMATION TAKEN FROM SUPPLIERS WEBSITE.
ALL RIGHTS RESERVED TO THEIR RESPECTIVE OWNERS.

Product supplier:

Devon Artificial Grass
20 Thatcher Avenue, Torquay
28 Sandoe Way, Westclyst, Exeter, Devon, EX1 3WJ

Email: info@devon-artificial-grass.co.uk
Phone: 01392 531411

General notes:

- Stride Treglown accept no responsibility for omissions and errors made in the production of this base line information or errors in new construction information deriving from the existing survey.
 - Drawing to be read in conjunction with all other relevant drawings and documents.
 - Main contractor to determine exact location of services/drainage, this should be confirmed on site prior to commencement of works to avoid tree pit / services conflicts.
 - Contractor to allow for white lining of parking bays.
 - All foundations and base formations to Engineers design and specifications.
 - All drainage details to Civil Engineers specification and details.
 - All manhole covers within paved areas to be recessed. Manhole covers are to withstand the appropriate loading class within any given area, manufacture and product details are to be confirmed with the Engineer and Landscape Architect.
 - External Lighting to Engineers detail and specification.
 - This drawing assumes that the existing site subsoil could be re-used.
 - All treatment of softwork areas to comply to BS4428 Code of Practice for general landscape operations.
 - All native shrub & hedge species plant type supplied for designated areas are to be determined by the proposed planting season. (ie bareroot or container grown stock).
 - Works described on this drawing include operations within or close to the root protection areas of very important trees. Excavation to be carried out in accordance with Arboricultural survey requirements.
- If in doubt, STOP and seek clarification.


Trulawn Adventure Artificial Grass by Devon Artificial Grass

Installation:

- Existing grass surface to be removed to a depth of 70mm.
- Across the entire area geotextile layer is required for ground stability.
- The entire perimeter is edged using 2x2 tanalised timber to ensure the sub-base material is supported.
- On the top of that type 1 limestone to be installed to a depth of 40mm.
- The ground to be compacted using a wacker plate to avoid sinkage and achieve a solid base.
- After that 25mm layer of sharp sand is added, levelled off and compacted again to ensure a smooth surface.
- A durable weed membrane should be installed to keep weeds from growing.
- The grass is then carefully rolled into position across the entire area and secured with small nails to the timber edge around the perimeter of the garden.

Responsibility is not accepted for errors made by others in scaling from this drawing.
All construction information should be taken from figured dimensions only.

0mm 50mm



Proposed location for Atrificial Grass Area.
Site Location Plan
Scale 1:200 @A3

D2 P33 08.06.2018 Landscape Tender Package

STATUS	REV	DATE	DESCRIPTION
--------	-----	------	-------------

CLIENT			REVISED BY
--------	--	--	------------

Council of the Isles of Scilly	Anna Tryka
--------------------------------	------------

	CHECKED BY
--	------------

	Dan Hutchinson
--	----------------

	ORIGINATOR NO
--	---------------

	150457
--	--------

CONSULTANT

STRIDE TREGLOWN

www.stridetreglown.com © Stride Treglown Limited 2016

PROJECT

Carn Gwavel
Church Road
St Mary's
Isles of Scilly
TR21 0NA

DRAWING TITLE

Artificial Grass

SUITABILITY STATUS	SCALE
D2 : SUITABLE FOR TENDER	N.T.S

PROJECT ORIGINATOR ZONE LEVEL TYPE ROLE CLASSIFICATION NUMBER	REVISION
150457-STL-XX-XX-DR-L-XXXX-09401	P33