

KEY:
To be read in conjunction with soft landscape specification and plans

1. Trees to be supplied and planted by Landscape Contractor in accordance with Planting Schedule and Specification

2. Bark mulch 1000mm dia. at 50mm depth, around all trees to be planted in grass areas

3. Underground anchor guying system

4. Aeration/irrigation pipe to be placed two third from the top of rootball

5. Center of tree pit to be marked with timber stake (minimum 1500mm), prior to tree planting

6. Imported topsoil laid in accordance with the Specification

7. Imported subsoil laid in accordance with the Specification

8. Compacted dome subsoil under rootbal

9. Where required 1000mm deep root barrier to be installed against edge of tree pit along the line of underground services, roads and footways.

10. Loosen and shape base to aid root penetration and pit drainage.

11. Existing surrounding soil

NOTE:
- Contractor is to comply with BS8545: 2014 Trees: from nursery to independence in the landscape – Recommendations, with regard to section 10.2 Considerations below ground.

- Root barrier is not to be wrapped around the rootball and only installed adjacent to services where needed - locations to be agreed with project civil and M&E engineers.

Works by the Main Contractor Notes:

Tree Pit Excavations:
Excavate pit to achieve desired width and depth of tree pit. Any stone, rubble, rubbish and other foreign debris that is exposed in the digging of the tree pits shall be removed from site.
Fork over the base and sides of tree pits to thoroughly loosen the soil and to relieve compaction to a minimum depth of 250mm. All smooth, glazed or compacted sides to tree pits shall be loosened by forking to encourage lateral rooting.

Subsoil layers around tree pits:
The contractor is to ensure that subsoil layers are free-draining. Drainage is to be installed at the discretion of the Landscape Contractor in the event of potential ponding or waterlogging in the base of the pits. French drains, or similar approved, to be installed in consultation with the Engineers.

Responsibility is not accepted for errors made by others in scaling from this drawing.
All construction information should be taken from figured dimensions only.

0mm 50mm

STATUS	REV	DATE	DESCRIPTION
D2	P33	08.06.2018	Landscape Tender Package

CLIENT
Council of the Isles of Scilly

REVISED BY
Anna Tryka

CHECKED BY
Dan Hutchinson

ORIGINATOR NO
150457

CONSULTANT
STRIDE TREGLOWN
www.stridetreglown.com
© Stride Treglown Limited 2016

PROJECT
Carn Gwavel
Church Road
St Mary's
Isles of Scilly
TR21 0NA

DRAWING TITLE
Tree Pit

SUITABILITY STATUS
D2 : SUITABLE FOR TENDER

SCALE
1 : 25 @ A3

PROJECT | ORIGINATOR | ZONE | LEVEL | TYPE | ROLE | CLASSIFICATION | NUMBER
150457-STL-XX-XX-DR-L-XXXX-09403

REVISION
P33