

Project No. 150457

Client: Council of the Isles of Scilly

Tender Issue 10/11/2017

STRIDE TREGLOWN
ARCHITECTURE

Carn Gwavel School

10 November 2017

This document includes:

Code	Section	Revision	Dated
P20	Unframed Isolated Trims/ Skirtings/ Sundry Items		

P20 Unframed Isolated Trims/ Skirtings/ Sundry Items

To be read with Preliminaries/ General conditions

- 201 MEDIUM DENSITY FIBREBOARD WINDOW SILL BOARDS - GENERALLY
- Manufacturer: Contractor's choice.
 - Product reference: Contractor's choice.
 - Standard: To BS EN 622-5.
 - Type: Primed MDF.
 - Formaldehyde class: To BS EN 622-1, Class E1.
 - Fire rating: To BS 476-7, Class 1.
 - - Thickness: 25 mm.
 - Finished size: Depth of window reveal plus 32mm, width of window plus 50mm. Refer to window schedule.
 - Edges: Quarter rounded.
 - Finish: Prepared, primed and decorated, as section M60, Satinwood finish.
 - Support/ Fixing: Plugged, screwed and pelleted @max 600mm centres.
- 202 MEDIUM DENSITY FIBREBOARD WINDOW SILL BOARDS - WET AREAS
- Manufacturer: Contractor's choice.
 - Product reference: Contractor's choice.
 - Standard: To BS EN 622-5.
 - Type: Moisture Resistant MDF.
 - Formaldehyde class: To BS EN 622-1, Class E1.
 - Fire rating: To BS 476-7, Class 1.
 - - Thickness: [25 mm].
 - Finished size: Depth of window reveal plus 32mm
 - Edges: [Quarter rounded].
 - Finish: Prepared, primed and decorated, as section M60, clause 150, Acrylic Eggshell.
 - Support/ Fixing: Plugged, screwed and pelleted @max 600mm centres.
- 203 MEDIUM DENSITY FIBREBOARD SKIRTINGS - GENERALLY
- Manufacturer: Contractor's choice.
 - Product reference: Contractor's choice.
 - Standard: To BS EN 622-5.
 - Type: Primed MDF.
 - Formaldehyde class: To BS EN 622-1, Class E1.
 - Fire rating: To BS 476-7, Class 1.
 - Profile: Bullnose.
 - Finished size: 19 x 150mm.
 - Finish as delivered: Prepared, primed and decorated, as section M60, clause 150, Acrylic Eggshell.
 - Fixing: Plugged, screwed and pelleted @ max 600mm centres.

205 MEDIUM DENSITY FIBREBOARD ARCHITRAVES - GENERALLY

- Manufacturer: Contractor's choice.
 - Product reference: Contractor's choice.
- Standard: To BS EN 622-5.
 - Type: Primed MDF.
 - Formaldehyde class: To BS EN 622-1, Class E1.
- Fire rating: To BS 476-7, Class 1.
- Profile: As Architects drawings.
 - Finished size: 18 x 69mm.
- Finish as delivered: Prepared, primed and decorated, as section M60, Satinwood finish.
- Fixing: Plugged, screwed and pelleted @ max 600mm centres.

206 MEDIUM DENSITY FIBREBOARD ARCHITRAVES - WET AREAS

- Manufacturer: Contractor's choice.
 - Product reference: Contractor's choice.
- Standard: To BS EN 622-5.
 - Type: Primed Moisture Resistant MDF.
 - Formaldehyde class: To BS EN 622-1, Class E1.
- Fire rating: To BS 476-7, Class 1.
- Profile: Square pencil round edge.
 - Finished size: 14 x 69mm.
- Finish as delivered: Prepared, primed and decorated, as section M60, Satinwood finish.
- Fixing: Plugged, screwed and pelleted @ max 600mm centres.

EXECUTION

510 INSTALLATION GENERALLY

- Joinery workmanship: As section Z10.
- Metal workmanship: As section Z11.
- Methods of fixing and fasteners: As section Z20 where not specified.
- Straight runs: To be in one piece, or in long lengths with as few joints as possible.
- Running joints: Location and method of forming to be agreed where not detailed.
- Joints at angles: submit proposals.
- Position and level: To be agreed where not detailed.