

Solar Garden Location Plan

1: 1250

PL PL03 16/07/2018 Proposed fence line/solar panels and site boundary line location updated.
PL PL01 31/05/2018 Issued for Planning

Responsibility is not accepted for errors made by others in scaling from this drawing.

All construction information should be taken from figured dimensions only.

STATUS REV DATE DESCRIPTION CLIENT

Hitachi Europe Ltd.

REVISED BY Margarita Janusevic CHECKED BY Edward Flood ORIGINATOR NO 151838

PL03


### **STRIDE TREGLOWN**

IoS Smart Island St Mary's Airport, 3 Hannover Ct, Isles of Scilly, TR21 ONG

Site Location Plan (Solar Garden)

SUITABILITY STATUS
S1: SUITABLE FOR CO-1: 1250@ A2 \_ORDINATION\_

PROJECT | ORIGINATOR | ZONE | LEVEL | TYPE | ROLE | CLASSIFICATION | REVISION 151838-STL-XX-ZZ-DR-A-XXXX-10007



Proposed Solar Garden Plan 1:500 Responsibility is not accepted for errors made by others in scaling from this drawing.

All construction information should be taken from figured dimensions only.

50mm 100mm

Key:

- Proposed Deer fence

PL PL03 16/07/2018 Proposed fence line/solar panels and site boundary line location updated.
PL PL02 07/06/2018 Plan updated to show proposed fence line.
PL PL01 31/05/2018 Issued for Planning

STATUS REV DATE DESCRIPTION

CLIENT REVISED BY

Margarita Janusevic

Edward Flood

ORIGINATOR NO

151838

CONSULTANT

# STRIDE TREGLOWN

IoS Smart Island
St Mary's Airport,
3 Hannover Ct,
Isles of Scilly,
TR21 ONG

DRAWING TITLE

Proposed Solar Garden Plan

SUITABILITY STATUS		SCALE
PL:SUITABLE FOR	As indic	ated @ A1
CO-ORDINATION		
PROJECT   ORIGINATOR   ZONE   LEVEL   TYPE   ROLE   CLASSIFICATION	NUMBER	REVISION
151838-STL-XX-ZZ-DR-A-XXXX-10	0009	PL03


# Airport Solar Garden



48.8kW Array, South orientation. Ten strings of 16 x 305Wp panels. Two 20kW 3phase dual MPPT inverters. Estimated annual generation of 49,000kWh


48.8kW South 49,000kWh Annual generation

# Array positioning



Note: Array spacing takes account of increase in slope as terrain falls away to the North.

### Dimensions




Elevation shows dimensions of one 'Table'. Solar Garden comprises three rows of tables. Due to variations in terrain, level of concrete footing above ground will differ depending on location. Height of tables is adjustable. Tables are shown adjusted to maximum height

48.8kW South 49,000kWh Annual generation

# Dimensions Dimensions

2800



Due to variations in terrain, level of concrete footing above ground will vary depending on location. Height of tables is adjustable. Tables are shown adjusted to maximum height

# Connection arrangement

The solar plant was originally intended to feed power to the IoS Airport infrastructure. After consultation with WPD, there were concerns that the connection point in the Airport may be vulnerable to voltage uplift during periods of low consumption and high solar generation. WPD have offered a new more 'robust' connection point in the adjacent field.

Solar PV cable to Point of Connection in green cabinet. Buried direct in trench, approximately 120m in length

WPD provided cable to Point of Connection in green cabinet

Proposed extent of fencing. 4m access gate in SE corner




IoS Smart Energy Islands Project

# Garden Airport

48.8kW South 49,000kWh Annual generation

Airport Solar Garden


## Point of Connection



Green cabinet housing WPD Point of Connection, isolation, cable protection and metering equipment. GRP construction, Green (RAL 14 C 39) gloss finish. Mounted on concrete plinth

## Schematic

24.4kW Photovoltaic array MPPT A Three strings 16 x 305Wp Panels MPPT B Two strings 16 x 305Wp Panels



### **GRID PROTECTION SETTINGS (G59/3)**

RoCoF

		-,
STAGE 1 OVERVOLTAGE	262V	1.0S
STAGE 1 UNDERVOLTAGE	200V	2.5S
STAGE 2 OVERVOLTAGE	274V	1.0S
STAGE 2 UNDERVOLTAGE	184V	0.5S
STAGE 1 OVERFREQUENCY	51.5Hz	90S
STAGE 1 UNDERFREQUENCY	47.5Hz	20S
STAGE 2 OVERFREQUENCY	52Hz	0.5S
STAGE 2 UNDERFREQUENCY	47Hz	0.5S
DISCONNECT ON LOSS OF MAII	NS	
VECTOR SHIFT	12 DEGRE	ES

0.2Hz/sec


The Total Installed Capacity of this system will be 48.8kW. The Declared Net Capacity will be 40kW

# ort Solar Garc

### **IoS Smart** Energy Islands **Project**

South 49,000kWh Annual generation

48.8KW



	VER CLASS				300	305	310		315	32
MIN	HMUM PERFORMANCE AT STANDA	ARD TEST CON	DITIONS, STC1	POWER TOLERANC	E+5W/-0W)					
	Power at MPP		PMP	[W]	300	305	310		315	32
Mini mum	Short Circuit Current		I <sub>sc</sub>	(A)	9.72	9.78	9.83		9.89	9.9
	Open Circuit Voltage <sup>1</sup>		V <sub>oc</sub>	[V]	39.48	39.75	40.02	4	0.29	40.5
Min	Current at MPP		IMPP	[A]	9.25	9.31	9.36		9.41	9.4
	Voltage at MPP		VHPP	[V]	32.43	32.78	33.12	3	3.46	33.8
	Efficiency <sup>1</sup>		η	[%]	≥17.8	≥ 18.1	≥ 18.4	≥	18.7	≥19
MIN	IMUM PERFORMANCE AT NORMA	L OPERATING	CONDITIONS, N	MOT <sup>2</sup>						
	Power at MPP		PMP	[W]	224.1	227.8	231.6	2	235.3	239
8	Short Circuit Current		l <sub>sc</sub>	[A]	7.83	7.88	7.92		7.97	8.0
Minimu	Open Circuit Voltage		Vec	[V]	37.15	37.40	37.66	3	7.91	38.1
Σ	Current at MPP		I <sub>MP?</sub>	(A)	7.28	7.32	7.37		7.41	7.4
	Voltage at MPP		VMP	(V)	30.78	31.11	31.44	3	1.76	32.0
MOMINAL	intertry standard for learning	evenueliei evenueliei	At least 93.1% At least 85% of All data within Full warranties	. 0.54% degradation of nominal power up f nominal power up measurement tolera in accordance with t	p to 10 years. to 25 years. nces, the warranty	BATIVE EFFICIENCY [52]				
COMPARED TO NOMINAL	Modely standed to brond	summeried 20 25 25 25 25 25 25 25 25 25 25 25 25 25	At least 93.1 % At least 85% of All data within Full warranties terms of the Q0 respective coun	. 0.54% degradation of nominal power up f nominal power up measurement tolera in accordance with I CELLS sales organiz	n per year, p to 10 years, to 25 years, nces, the warranty	Phice of the less	200 400 I module perform	nance under l	RRADIANCE (W	e conditions
MALANIA COMPARED TO NOMINAL	To the state of the second of	20 26 YEARS	At least 93.1 % At least 85% of All data within Full warranties terms of the Qr respective coun	0.54% degradation of nominal power up in nominal power up in nominal power up measurement tolera in accordance with ELLS sales organizatry.	i per year. plo 10 years. plo 10 years. to 25 years. noes. the warranty ation of your	ASS 100	I module perform	nance under l ditions (25°0	RRADIANCE (W	(/m²) ce conditions i n²).
TENTIAN DE L'ANNO LE L'ANNO L'ANNO LE L'ANNO L'ANNO LE L'ANNO LE L'ANNO LE L'ANNO LE L'ANNO LE L'ANNO LE L'ANNO	In the state of the second of	20 25 YEARS	At least 93.1 % At least 85% of All data within Full warranties terms of the Qu' respective cour	0.54% degradation of nominal power up in nominal power up measurement tolera in accordance with IZELLS sales organizatry.  + 0.04	per year, to 10 years, to 25 years, noes, nees, the warranty ation of your	Typica compa	I module perform rison to STC con β	nance under I ditions (25°C	IRRADUNCE(W low imadiano C. 1000 W/n	oe conditions in 9.
TEM Tem Tem	In the state of the second of	20 26 YEARS	At least 93.1 % At least 85% of All data within Full warranties terms of the Qr respective coun	0.54% degradation of nominal power up in nominal power up in nominal power up measurement tolera in accordance with ELLS sales organizatry.	per year, to 10 years, to 25 years, noes, nees, the warranty ation of your	ASS 100	I module perform rison to STC con β	nance under l ditions (25°0	IRRADUNCE(W low imadiano C. 1000 W/n	oe conditions in 9).
TEM Tem	In the control of the	20 26 YEARS	At least 93.1 % At least 85% of At least 85% of Atl data within Full warranties terms of the QV respective country [96/K]	0.54% degradation of nominal power up in nominal power up measurement tolera in accordance with IZELLS sales organizatry.  + 0.04	n per year, pto 10 years, to 25 years, to 25 years, noes, the warranty ation of your  Temperature C  Normal Operat	Typica compa	I module perform rison to STC con β	nance under I ditions (25°C	IRRADUNCE(W low imadiano C. 1000 W/n	(/m²) ce conditions i n²).
TEM Tem Tem Max	In the state of the second of	39 39 39 TEARS TEARS OF YEARS	At least 93.1 % At least 85% of At least 85% of Atl data within Full warranties terms of the QV respective country [96/K]	0.54% degradation of nominal power up of nominal power up measurement tolera in accordance with CELLS sales organizity.  + 0.04  - 0.37	per year, to 10 years, to 25 years, noes, nees, the warranty ation of your	Typica compa	I module perform rison to STC con β	(%/K)	RRADUNCE(W low irradians C. 1000 Wm	ce conditions in %.  -0.2  6.4 (43 ± 3 ° 0
TEN Tem PR Max Max	In the control of the	30 35 35 35 45 YEARS ON Y	At least 93.1 % At least 85% of At least 85% of Atl data within Full warranties terms of the QV respective country [96/K] [96/K] [96/K]	0.54% degradation of nominal power up of nominal power up measurement tolera in accordance with CELLS sales organizery.  + 0.04 - 0.37	per year, per year, per year, to 25 years, to 25 years, to 26 years, the warranty stion of your  Temperature C Normal Operat  Safety Class Fire Rating	Typica compactoring Module Temperature	I module perform rison to STC con β	19   19   19   19   19   19   19   19	IRRADUNCE(W low imadiano C. 1000 W/n	.ce conditions = 0.2 (43 ± 3 °4 (40 ± 5°F).
TEN Tem Tem Max Max Max	In the state of the second of	38 38 WE NOT 4 YE ARES (V)  [A DC]  [Ibs/ft²]	At least 93.1 % At least 93.1 % At least 85% of All data within Full warranties terms of the Q4 respective country [96/K]  [96/K]  1000 (IE	0.54% degradation of nominal power up of nominal power up measurement tolera in accordance with CELLS sales organizery.  + 0.04 - 0.37	per year, to 20 years, to 20 years, to 20 years, to 20 years, the warranty stion of your  Temperature C Normal Operat  Safety Class Fire Rating Permitted model	Typica compactoring Module Temperature duty	I module perform rison to STC con β	19   19   19   19   19   19   19   19	Reabunce(Windland Co. 1000 Windland Co. 1000 Win	.ce conditions in °).  -0.2  .4 (43 ±3 °(

Number of Modules per Pallet UL 1703; VDE Quality Tested; CE-compliant; IEC 61215:2016; IEC 61730:2016, Application class A 32 Number of Pallets per 53' Trailer 30 Number of Pallets per 40' High Cube Container Pallet Dimensions (L × W × H) 69.3 in × 45.3 in × 46.9 in

NOTE: Installation instructions must be followed. See the installation and operating manual or contact our technical service department for further information on approved installation and use of this product.

Haawha Q CEUS America Inc.
300 Spectrum Center Drive, Suite 1250, Invine, CA 92618, USA I TEL +1 949 748 59 961 EMAIL inquiry@us.q-cells.com ( WEB www.q-cells.us

(1760mm × 1150mm × 1190mm)

1415 lbs (642 kg)

# Q.ANTUM DUD Q.PEAK DUO BLK-G5 300-320 **Q.ANTUM SOLAR MODULE**

The new Q.PEAK DUO BLK-G5 solar module from Q CELLS impresses with its outstanding visual appearance and particularly high performance on a small surface thanks to the innovative Q.ANTUM DUO Technology. Q.ANTUM's world-record-holding cell concept has now been combined with state-of-the-art circuitry half cells and a six-busbar design, thus achieving outstanding performance under real conditions — both with low-intensity solar radiation as well as on hot, clear summer days.



### Q.ANTUM TECHNOLOGY: LOW LEVELIZED COST OF ELECTRICITY

Higher yield per surface area, lower BOS costs, higher power classes, and an efficiency rate of up to 19.3%.



### INNOVATIVE ALL-WEATHER TECHNOLOGY

Optimal yields, whatever the weather with excellent low-light and temperature behavior.



Long-term yield security with Anti LID Technology, Anti PID Technology<sup>1</sup>, Hot-Spot Protect and Traceable Quality Tra.Q™.



High-tech aluminum alloy frame, certified for high snow (5400 Pa) and wind loads (4000 Pa) regarding IEC.



### A RELIABLE INVESTMENT

Inclusive 12-year product warranty and 25-year linear performance guarantee2.



### STATE OF THE ART MODULE TECHNOLOGY

Q.ANTUM DUO combines cutting edge cell separation and innovative wiring with Q.ANTUM Technology.



### THE IDEAL SOLUTION FOR:





APT test conditions according to IEC/TS 62804-1:2015, method B (-1500V, 168h)

See data sheet on rear for further

ANTI PID TE CHROLOL
(AJT)

NOT-SPOT PROTECT
(SSP)

TRACEABLE QUALITY
(TRAS 14)

ANTILUD TECHNOLOL
(ALT)

### Recommendations for ecological improvements to Solar Farm at St Mary's Airport

### 1. Planting of new native hedgerow:

- Species need to be tolerant of slightly acid soils (pH5 ideally), salt and wind
- 40-60cm growth form will establish quicker than taller specimens
- Planted in a double row approximately 160mm apart
- Use of biodegradable shelters will assist in protecting the young 'whips' from the elements and grazing rabbits so these will assist establishment
- Use of a biodegradable mulch mat to suppress weed growth will assist with establishment of trees further.
- All species can readily be coppiced or laid to control the maximum height of 2m

Species	Size	% in hedge	Benefits to Wildlife	Time to plant
Hawthorn	40-60cm	60%	Flowers in May prolonging the nectar season further. It is a species that supports up to 300 species of insect and their associated prey such as hoverflies. The fruits are eaten by a variety of birds including winter Thrushes.	November - March
Blackthorn	40-60cm	20%	Flowers in March and April (after Hazel) providing a continued source of nectar for a variety of late emerging solitary bees. Leaves are important for caterpillars of moths including Magpie and Common Emerald, which are a food source for Pipistrelle bats. Fruits are eaten by a variety of birds including Blackbirds and Greenfinches.	November – March
Hazel	40-60cm	10%	Flowers from mid-February providing nectar for bees such as Buff-tail and Early Bumblebee. Leaves are important for moth caterpillars such as Large Emerald, White Wave, Barred Umber and Nut-tree Tussock. Fruits are eaten by birds such as Blue and Great Tits	November – March
Field Maple	40-60cm	5%	Flowers are inconspicuous in spring. Field Maple is very attractive to aphids and therefore their prey including hoverflies and a variety of insectivorous birds. Its leaves are favoured by moth caterpillars including Maple pug, Small Yellow Wave and the Prominent which are prey for a variety of species of bat.	November – March
Buckthorn	40-60cm	5%	Main foodplant for Brimstone Butterfly. It flowers in March and provides an early source of nectar for a variety of insects, whilst its fruits are eaten by a variety of birds. Its dense growth form is ideal for nesting birds	November - March

### Approximate costs per metre for planting

Materials (including trees and all protection) - £15.50 per metre (does not include delivery or VAT)

Labour - 3 man days

www.ios-wildlifetrust.org.uk Charity number: 1097807

### Isles of Scilly Wildlife Trust

### **Ongoing maintenance**

- Expect to replace 10 12.5% of whips annually for the 1<sup>st</sup> two years of establishment (approximately 8m per year) this should be done from **October to March**
- Expect to replace and re-insert plastic pegs from mulch mat when needed
- Weed at base of trees (hand-pulling only) 3 times per year (May, July & August)

### Approximate annual costs for maintenance:

Labour - Replacement of dead/dying trees - 1man day

Labour - Hand-weeding three times annually - 1.5 man days

Labour – replace/re-insert pegs - 1 man day

Materials – see above for costs (does not take into consideration inflation, delivery or VAT)

### 2. Enhancement & establishment of wild flower meadow:

The eastern part of the site (nearest the car park) shows some build-up of thatch and areas of bare ground. The remainder of the site has a well-established sward and a significant build-up of thatch. The site appears to be regularly mown with the cuttings left on site, hence the thatch. The wildflower species and grasses recorded on the site survey reflect those that resemble MG5 *Cynosurus cristatus – Centaurea nigra* grassland (for species list see end of report). This grassland type is now relatively rare on Scilly and as such, these management prescriptions are based on enhancing the current species composition, rather than creating a totally new meadow.

Timing	Grassland enhancement
Year 1	
Late July	Keep the sward short (3-5cm) by close mowing
	(remove cuttings from site)
August	Power harrow, disc or rake the grass surface to
	expose 30-50% bare ground, or localise
	cultivation in small patches or strips
	Spot spray (Round-up) 10 blocks of 1 square
	metre
September to October	Sow wildflower seed thinly onto exposed soil
	and lightly roll to ensure seed contact with soil
October to March (Years 1 into 2)	Keep the grass short (<10cm) by mowing in
	autumn and again in spring. Plant 100 plug
	plants – All arisings to be moved off site
Year 2	

Charity number: 1097807

www.ios-wildlifetrust.org.uk

### Isles of Scilly Wildlife Trust

April to July	Control annual weeds by topping (no lower than 10cm), pulling or spot-treatment (perennial weds) – All cuttings to be moved off -site
July to September	Mow the sward to 5-10cm for the remainder of the growing season – All cuttings to be moved off site
Year 3 onwards	
Establish the future management regime i.e. hay meadow	Hay meadow: cut for hay in early to late August. Mow again from September to December (so long as ground conditions permit) to maintain a 5-10cm sward height. All cuttings to be moved off site

### **Species composition:**

To enhance the current species composition, sow using seed from 10 key individual species, rather than a standard wildflower/grassland seed mix. The sowing rate should be based on 4g per square metre for approximately 1, 350 square metres and totalling 5.4kg of seed.

An 11<sup>th</sup> species Pignut (*Conopodium majus*) a rare species in Scilly that forms part of the MG5 grassland composition, grows from tubers. Therefore, it is recommended that plug plants are used to incorporate this species into the sward. This can be achieved by spot treating a 1 sqm block of grassland to remove competition and then plant at a rate of 1 per 10 sq m (10 per block). It is recommended that 10 blocks scattered throughout the area would be sufficient to help establish this species. Plant plugs between October and March.

The species of interest that should be included in the mix are:

Common Name	Scientific Name	Flowering period	No. of grams required
Common Cat's Ear	Hypochaeris radicata	June to September	540g
Black (Common)	Centaurea nigra	July to September	540g
Knapweed			
White Clover	Trifolium repens	June to September	540g
Red Clover	Trifolium pratense	May to Sepember	540g
Common Sorrel	Rumex acetosa	May to June	540g
Sheep's Sorrel	Rumex acetosella	May to August	540g
Yarrow	Achillea millefolium	June to August	540g
Lady's Bedstraw	Galium verum	July to August	540g
Bird's foot Trefoil	Lotus corniculatus	June to September	540g
Crested Dog's-tail (grass)	Cynosurus cristatus	June to August	540g
Pignut	Conopodium majus	May to June	100 plug plants

www.ios-wildlifetrust.org.uk Charity number: 1097807

### Isles of Scilly Wildlife Trust

### Costs per metre for meadow enhancement

Materials (including seed and sand) - £0.54 per square metre\* (does not include delivery or VAT)

Materials (includes chemical and plug plants) - £0.77 per square metre (does not include delivery or VAT)

Labour (harrowing, sowing and rolling only) – 2 man days

Labour (spot spray 100 square metres and plant 100 plug plants) – 1.25 man days

Labour (mowing and removal of cuttings); Yr. 1 - 1.5 man days minimum (minimum of 3 cuts).

Labour (mowing/topping and removal of cuttings); Yr. 2 - 2man days minimum (minimum of 4 cuts per year).

Labour (mowing and removal of cuttings); Yr. 3 onwards - 1 man day (minimum of 2 cuts).

\* at time of pricing Sheep Sorrel was out of stock, so price for this species is not included.

www.ios-wildlifetrust.org.uk Charity number: 1097807